

BATT-36V-C

3.6V Lithium Battery (C-Size)

Primary, C-size bobbin cell, non-rechargeable battery. It contains non-flammable electrolyte and is UL recognized. Durable battery used on most meters that accept C-size batteries. Sustains battery life more than 10 years depending on application use. Provides higher power and energy and has superior drain capability.



Features

- High and stable operating voltage
- Higher power and higher energy for the whole battery life
- Superior drain capability
- Higher power applications
- Low self-discharge rate (less than 1% after 1 year of storage at +20°C)
- Battery life higher than 10 years, depending on the application
- Hermetic glass-to-metal sealing
- Avoid leakage, key for a higher than 10 year battery life
- Non-flammable electrolyte
- Safer operation in case of abuse
- Complete with one 3.6V Lithium C-size battery

Specifications

Cell Type	Primary, non-rechargeable
Chemistry	Lithium Thionyl Chloride
Voltage Range	2.0 to 3.7V
Nominal Voltage	3.6V
Nominal Capacity	9Ah @ 2mA to 2.0V @ 23°C
Max. Continuous Discharge Current	200mA continuous
Max. Pulse Discharge Current	Up to 400mA (life and temperature dependent)
Exterior/Housing	Stainless steel container
Terminals/Connector	Radial tabs / radial pins / axial leads / flying leads
Weight	2oz (55g)

Ordering

BATT-36V-C3.6V Lithium Battery (C-Size)



UPC Code: 793950740361